



XP-350B/350BM

Thermal Barcode Printer

- Compact and space saving design
- Easy paper load with adjustable paper guide
- Printing speed up to 152mm per second
- Max 80mm label diameter, external amount and board option
- Thermal sensitive resistance, photoelectric sensor black mark sensor
- USB+Serial+ethernet all in one interface

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

XP-350B/350BM

Desktop Barcode Printer



Printing Features		XP-350B	XP-350BM
Resolution		203 DPI (8 dots/mm)	
Printing method		Direct Thermal	
Print speed		152mm/s Max.	
Max.print width		Max.76 mm	
Media			
Media type		Thermal paper/Thermal stickers paper	
Media width		20~82 mm	
Media thickness		0.06 ~ 0.19 mm	
Media roll diameter		Max.100 mm	
Performance Features			
Memory		DRAM:4M FLASH:4M	
Interfaces		USB+Serial	USB+Serial+Lan
Sensors		Print head temperature sensor / Cover open / Paper end / Gap	
Drawer port		1 ports (Pin 2 for cashdrawer)	
Fonts/Graphics/Symbologies			
Character sizes		Font 0 to Font8	
1D barcode		CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14	
2D bar code		PDF417 / QR CODE / DATMATRIXSPL	
Emulation		TSPL, ESC/POS	
Physical Features			
Dimension		220*148*150mm (D×W×H)	
Weight		1.44 kg	
Reliability			
Print head life		100 km	
Software			
Driver		Windows / Linux / Mac / Android	
Power supply			
Input		DC 24V/2.5A	
Environmental Conditions			
Operation		5 ~ 45°C, 20 ~ 80%RH	
Storage environment		-40 ~ 55 °C, ≤93%RH(40°C)	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

